

# LussoCrete



Industrial concrete look for new construction and renovation



## Colored Cementitious Micro-Topping

### ■ Features

**LussoCrete** is a polymer modified cementitious microtopping with a thickness of only 2mm.

**LussoCrete** provides a decorative coating with great mechanical characteristics.

**LussoCrete** gives a rich and mineral look.

**LussoCrete** is available in more than 60 colors.

### ■ Benefits

- No shrinkage - High abrasion resistance
- Excellent bonding properties
- Modern, Highly appreciated by architects
- High traffic (pedestrian and vehicles)
- Multiple finishing effects

### ■ Performances

- Abrasion test TABER (NF EN ISO 5470-1), loss at 28 days: 0,86 g
- Surface hardness test (NF EN 13892-6), point load : 0,034 mm at 28 days - at 14 days hardness : 31 N/mm<sup>2</sup> - at 28 days hardness : 42 N/mm<sup>2</sup>.

### ■ Areas of Application

**LussoCrete** is recommended in renovation over tiles, screeds, concrete but can also be used on new construction.

**LussoCrete** is also applicable on furniture

1. Old concrete renovation
2. New construction
3. Interior
4. Private homes
5. Hotels
6. Restaurants
7. Offices
8. Public areas
9. Furniture

# LussoCrete



Industrial concrete look for new construction and renovation

## ■ Description

### Characteristics:

**LussoCrete** system is composed of a main colored coat, sealer and wax:

1. Main colored coat: LussoCrete powder mixed with Lusso Binder and Lusso Pigment
2. Sealer: Lusso Color Protector, Lusso PU Sealer
3. Wax: Lusso Glossy or Matt Wax

### Packaging:

Product	Packaging
LussoCrete powder	25 kg
Lusso Binder	20 L
Lusso Pigment	250 g / 500 g / 1 kg
Sealer	10 L or 5 kg
Wax	5 L

## ■ Directions for use

### Substrate

- New substrate: Concrete slabs – Adhesive inserted or integrated screed or floating mortar screed – Dry screed – Liquid screed – Grout Floating radiating or water-heated or reversible cool-water flooring.
- Concrete flooring.
- Old substrate: old concrete, old tiling, old paint.
- Other substrate: wood (MDF, marine chipboard), furniture
- Other particular substrate: upon query.

### Application

•Application should be done according to READYMIX QATAR recommendation and may require training or support to the application team.

Because local job conditions vary, please contact your local READYMIX QATAR sales representative for further assistance.



### Precaution:

The application of **LussoCrete** requires tools and the proper training to achieve the best result. Please contact your local READYMIX QATAR representative for tools and training.

•Application timing may vary depending on the local conditions, especially temperature and humidity.

•Please refer to each product TDS for storage conditions and use precaution. Store all products in dry and limited sun exposure.

## ■ Safety

Please refer to each material safety data sheets for information prior to use.

Developed in partnership with



# LussoCrete



## Color Chart

### GREY SHADES

<b>Volcan intense</b>	<b>Volcan medium</b>	<b>Volcan light</b>
<b>Noir de vigne intense</b>	<b>Noir de vigne medium</b>	<b>Noir de vigne light</b>
<b>Acier intense</b>	<b>Acier medium</b>	<b>Acier light</b>
<b>Loft intense</b>	<b>Loft medium</b>	<b>Loft light</b>
<b>Galet intense</b>	<b>Galet medium</b>	<b>Galet light</b>

### BEIGE & BROWN SHADES

<b>Noisette intense</b>	<b>Noisette medium</b>	<b>Noisette light</b>
<b>Taupe intense</b>	<b>Taupe medium</b>	<b>Taupe light</b>
<b>Café crème intense</b>	<b>Café crème medium</b>	<b>Café crème light</b>
<b>Chypre intense</b>	<b>Chypre medium</b>	<b>Chypre light</b>
<b>Coton intense</b>	<b>Coton light</b>	

**Caution**

This chart is only a representation and does not guarantee an exact color. Colors can be significantly altered by the jobsite conditions and the tool used.

## COLD SHADES

Lavande intense	Lavande medium	Lavande light
Bermudes intense	Bermudes medium	Bermudes light
Océan intense	Océan medium	Océan light
Wimbeldon intense	Wimbeldon medium	Wimbeldon light

## WARM SHADES

Cape Town intense	Cape Town medium	Cape Town light
Chabby intense	Chabby medium	Chabby light
Violette intense	Violette medium	Violette light
Bordeaux intense	Bordeaux medium	Santorin intense
Santorin medium		

## CREAMY SHADES

Vanille intense	Vanille medium	Vanille light
Dune intense	Dune medium	Dune light

## TONIC SHADES

Violet pop intense	Rosso intense	Vert transat intense
Violet pop light	Rosso light	Vert transat light
Soleil intense	Cassis intense	Rose bonbon intense
Soleil light	Cassis light	Rose bonbon light
Pumpkin intense	Pumpkin light	

### Caution

This chart is only a representation and does not guarantee an exact color. Colors can be significantly altered by the jobsite conditions and the tool used.

# LussoCrete



Industrial concrete look for new construction and renovation

## ■ LussoCrete application examples



Floor



Wall



Furniture

## ■ LussoCrete jobsite example



### READYMIX QATAR LLC

Bldg No 385, Zone 32 St No 380, Al Makhiya St Madinat Khalifa  
North, Doha, PO Box 5007

Tel: (+974) 44341796 / (+97) 44241798

rmq.sales@lafargeholcim.com – www.readymixqatar.com.qa

The information contained in this document is given to the best of our knowledge and is the result of extensive and controlled testing. However, it cannot under any circumstances be considered as a warranty involving our liability in the case of misuse. Tests should be conducted before the product is used to ensure that the methods and conditions of use of the product are satisfactory. Our specialists remain at the disposal of customers if they require help with the application of the product for their specific needs.